

DAFTAR PUSTAKA

- Baytok, Y. M., Erek, A., & Saf, O. (2023). Numerical Estimation of Film Thickness With an Air-Assisted Spray Gun. *Engineering Transactions*, 71(2), 241–263. <https://doi.org/10.24423/EngTrans.3075.20230418>
- Fauzi, I., & Ardiansyah, F. (2024). Analisis Kebutuhan Material Blasting dan Painting Pada Reparasi Pengecatan Lambung Kapal Tongkang PSB 3002. *Techno Bahari*, 11(1), 50–58. <https://doi.org/10.52234/tb.v11i1.205>
- Francis, R. A. (2009). Through thick and thin: Some observations on dry film thickness of paint coatings. *49th Annual Conference of the Australasian Corrosion Association 2009: Corrosion and Prevention 2009*, 846–856.
- Kristanto, Y., Rubiono, G., & Mujiyanto, H. (2017). *Pengaruh Diameter Nossel Spraygun*. 2(1), 5–8.
- New Products & Services Jotun Introduces Next-Gen Polyurethane Topcoat Built-In Metal Protection for Lightweight , Compact*. (2025). November, 2025.
- Ningrum, A. P., Resmi, F., Khaqiqi, A. S., Teknik, J., Kapal, B., Perkapalan, P., & Surabaya, N. (2025). *ANALISIS PENGARUH PERBEDAAN UKURAN NOZZLE PADA*.
- No, V., Pratikno, H., Danielle, R., & Lalitya, W. (2025). *Analysis of Abrasive Materials dan Air Pressure Variations for Thermal Spray Aluminum Coating on Adhesion Strength and Corrosion Resistance in Seawater Environment*. 9(1), 1–6.
- Piter, F. E. O. F. (2022). *Analisis Prosedur Perawatan Kapal Dalam Hal*.
- Purnavita, S., Oktaviananda, C., Rinihapsari, E., Wibowo, P., & Primahendra, Y. B. S. (2023). Pengaruh Jumlah Pengemulsi pada Pembuatan Cat Emulsi Berbasis Bahan Alami Kasein dari Susu Sapi. *Metana*, 19(1), 13–20. <https://doi.org/10.14710/metana.v19i1.52473>
- Riyan, M., Rizqi, A., & Yunitasari, B. (2023). *Pengaruh Jarak Spray Coating Pada Baja SS400 Terhadap Laju Korosi Di Laut*.
- Roziqin, M., & Hardjito, A. (2024). Analisis Temperatur Benda Kerja Terhadap Kekerasan Cat Pada Proses Pengecatan Fabrikasi Metal Ducting. *Journal of Mechanical Engineering*, 1(3), 1–10. <https://doi.org/10.47134/jme.v1i3.3152>
- Settles, G. (1997). A flow visualization study of airless spray painting. *ILASS-Americas 10th Annual Conference on Liquid ...*, 145–149. <http://www.me.psu.edu/psgdl/Pubs/1997-Settles-CLASS.pdf>

Standard Test, & ASTM 4212 Viscosity Standard Test, V. by D.-T. V. S. T. (1999).
Standard Viscosity Test Method for by Dip- Type Viscosity Cups 1. 14, 1–6.

Wahyudi, D., Prasetyawati, D., Rohman, I., & Herdianti, W. A.(2025). Penilaian Resiko Keselamatan Kerja Pada Proses Reparasi Kapal Di Galangan PT.X dengan Metode HIRARC. *AGREGAT*, 1405-1410

Wang, Y. A., Xie, X. P., & Lu, X. H. (2020). Design of a double-nozzle air spray gun and numerical research in the interference spray flow field. *Coatings*, 10(5). <https://doi.org/10.3390/COATINGS10050475>

Y. SureshbabU, Sudharsan, K., Abinav, M., Barath, G., & Balasubramani, S. (2025). Optimization of spray-painting process parameters: A review. *AIP CONFERENCE PROCEEDINGS*, 3204, 0400. <https://doi.org/10.1063/5.0246685>

